

IP65 HE Etanj LED Armatür



Özellikler

- 160lm/W' a varan ultra verim
- Kırpışmasız
- IP65
- 18.400 lm'e kadar
- %60 enerji tasarrufu
- Aktif PFC >0.9, THD<%20
- Alüminyum soğutucu
- Darbe dayanımlı PC ön kapak
- H05SSF giriş kablosu
- EN60598 sertifikalı
- 3000K, 4000K, 6500K, CRI >80
- Min 50.000 açma/kapama

dayanımı

Ürün ID	Giriş Voltajı V	Güç	PFC	Ömür Saat	Çalışma Sıcaklığı	Işık Akısı	Boyutlar			Ağırlık	Ön Kapak
							A	B	C		
HE03-042-XXFIG	220-240V	9.0W	0.90	50.000	-20C +45C	1100LM	340	32	54	300gr	Opal
HE06-084-XXFIG	220-240V	17.0W	0.90	50.000	-20C +45C	2300LM	655	32	54	400gr	Opal
HE07-120-XXFIG	220-240V	25.0W	0.90	50.000	-20C +45C	3300LM	758	32	54	500gr	Opal
HE09-105-XXFIG	220-240V	20.0W	0.90	50.000	-20C +45C	3750LM	894	32	54	500gr	Opal
HE12-180-XXFIG	220-240V	29.0W	0.90	50.000	-20C +45C	4000LM	1240	32	54	800gr	Opal
HE12-180-XXTIG	220-240V	29.0W	0.90	50.000	-20C +45C	4400LM	1240	32	54	800gr	Transp.
HE12-200-XXFIG	220-240V	36.0W	0.90	50.000	-20C +45C	5000LM	1210	32	54	800gr	Opal
HE12-200-XXTIG	220-240V	36.0W	0.90	50.000	-20C +45C	5500LM	1210	32	54	800gr	Transp.
HE12-210-XXFIG	220-240V	41.0W	0.90	50.000	-20C +45C	5750LM	1210	32	54	800gr	Opal
HE12-210-XXTIG	220-240V	41.0W	0.90	50.000	-20C +45C	6325LM	1210	32	54	800gr	Transp.
HE15-273-XXFIG	220-240V	36.0W	0.90	50.000	-20C +45C	5000LM	1490	32	54	900gr	Opal
HE15-273-XXTIG	220-240V	36.0W	0.90	50.000	-20C +45C	5500LM	1490	32	54	900gr	Transp.
HE15-285-XXFIG	220-240V	52.0W	0.90	50.000	-20C +45C	7100LM	1540	32	54	1000gr	Opal
HE15-285-XXTIG	220-240V	52.0W	0.90	50.000	-20C +45C	7800LM	1540	32	54	1000gr	Transp.
HE15-286-XXFIG	220-240V	58.0W	0.90	50.000	-20C +45C	8400LM	1540	32	54	1000gr	Opal
HE15-286-XXTIG	220-240V	58.0W	0.90	50.000	-20C +45C	9240LM	1540	32	54	1000gr	Transp.
HE12-200-XXFI2	220-240V	72.0W	0.90	50.000	-20C +45C	9700LM	1210	97	54	1900gr	Opal
HE12-200-XXTI2	220-240V	72.0W	0.90	50.000	-20C +45C	11000LM	1210	97	54	1900gr	Transp.
HE15-286-XXFI2	220-240V	116W	0.90	50.000	-20C +45C	16400LM	1540	97	54	2100gr	Opal
HE15-286-XXTI2	220-240V	116W	0.90	50.000	-20C +45C	18480LM	1540	97	54	2100gr	Transp.

Uygulamalar


- Fabrika, depo, otopark, makina içi, soğuk hava depoları

Opsiyonlar


- 2700K, 5700K
- DALI
- Özel kablo boyu, konektör
- 90 CRI

IK08 IP65 CE 850°C

Işık Dağılımları



Opal



Transparan

Boyutlar

